

# MBD3037-0805-2 Planar Tunnel Diode




## Technical Characteristics

Product Features
Rugged Germanium Planar Construction
Excellent Temperature Stability
No DC Bias Required
Wide Video Bandwidth

Product Description
EclipseMDI MBD3037-0805-2, is a zero-bias, rugged Planar Tunnel Diode constructed with Germanium Planar. This tunnel diode exhibits excellent temperature stability, wide video bandwidth.


Maximum Ratings
Storage Temperature.....-65° to +125°C
Operating Temperature.....-65° to +110°C
Input Power Handling.....+17dBm CW or 3 ERG spike
Soldering Temperature.....+160° C

## 0805-2 (non-hermetic)




Parameters	Specifications				
	Conditions	MIN	Typical	MAX	UNITS
$I_p$		250		300	$\mu A$
$C_j$	$V_r = V_v$ , $f = 100 \text{ MHz}$			.30	pF
$K[Y]$	$P_{in} = -20 \text{ dBm}$ $R_{Load} = 10 K$ , $f = 10 \text{ GHz}$		650		mV/mW
$R_v$			130		$\Omega$ Ohms
$I_p/I_v$		2.5			
$V_r$	$I_f = 500 \mu A$		410		mV
$V_f$	$I_f = 3 \text{ mA}$			130	mV

## Diode equivalent circuit



## Back diode parameters



## About EclipseMDI

ECLIPSE Microdevices is located in San Jose, California. ECLIPSE has been developing high performance analog semiconductors for use in wireless radio frequency (RF), microwave, and millimeter wave for commercial and industrial applications. ECLIPSE has formed a strategic alliances - with foundries that features leading state-of-the-art process technologies and with manufacturing facilities for high-volume production of innovative RFIC's.

## Product Export Classification

ECCN: EAR 99 (unless otherwise specified)  
HTS: 8542330000