

ESS1826A3 Biased Schottky Diode Detector

SMA-F/SMA-M Negative Output Polarity
18.0 to 26.0 GHz Octave Band



Technical Characteristics

Product Features
High Dynamic Range @100 uA typ. bias
Flat Frequency Response
Ultra Wideband and Ultra fast
Low Video Output Resistance (350 ohms typ.)
Negative Polarity is Standard
High Reliability Hermetically Sealed Coax
RoHS Compliant


Max. Ratings	
Storage Temperature:	-65°C to +125°C
Operating Temperature:	-55°C to +90°C
Maximum input power:	200mW

Electrical Specifications

Parameters	Freq. (GHz)	Min.	Typical	Max.	Units
Voltage Sensitivity	18.0 to 26.0 GHz		1000		mV/mW
Bias			100		µA
Tangential Sensitivity (Note 1)	18.0 to 26.0 GHz		-52		dBm
Flatness	18.0 to 26.0 GHz		0.25		+/-dB
Video Capacitance			10		pF
CW Power Handling				200	mWatts
Operating Temperature		-55		125	°C

- NOTES:
- 1. TSS is measured with a 2 MHz video bandwidth and 2dB NF amplifier.
 - 2. Typical values are measured at +25°C and are not guaranteed.
 - 3. At -20dBm input power.
 - 4. Add "P" to model for positive polarity, ex. ESS1826PA3

Outline Drawing



Product Export Classification
ECCN: EAR 99 (unless
otherwise specified)
HTS: 8541.10.0060

