

MBD2057-H20 Planar Tunnel Diode




Technical Characteristics

Product Features
Rugged Germanium Planar Construction
Excellent Temperature Stability
No DC Bias Required
Wide Video Bandwidth


Product Description
EclipseMDI MBD2057-H20, is a zero-bias, rugged Planar Tunnel Diode constructed with Germanium Planar. This tunnel diode exhibits excellent temperature stability, wide video bandwidth. The MBD2057 is also available in a non-hermetic (H20X) ceramic packages.

Maximum Ratings
Storage Temperature.....-65° to +125°C
Operating Temperature.....-65° to +110°C
Input Power Handling.....+17dBm CW or 3 ERG spike
Soldering Temperature.....+160° C




Parameters	Specifications				
	Conditions	MIN	Typical	MAX	UNITS
I _p		200		300	μA
C _j	V _r =V _v , f=100MHz			.30	pF
K[Y]	Pin=-20dBm R _L (Load)=10K, f=10GHz		750		mV/mW
R _v			130		Ω Ohms
I _p /I _v		2.5			
V _r	I _f =500μA		410		mV
V _f	I _f =3mA			130	mV

Diode equivalent circuit



Back diode parameters



About EclipseMDI

ECLIPSE Microdevices is located in San Jose, California. ECLIPSE has been developing high performance analog semiconductors for use in wireless radio frequency (RF), microwave, and millimeter wave for commercial and industrial applications. ECLIPSE has formed a strategic alliances - with foundries that features leading state-of-the-art process technologies and with manufacturing facilities for high-volume production of innovative RFIC's.

Product Export Classification
ECCN: EAR 99 (unless otherwise specified) HTS: 8541.10.0060

