

MBD3057-H20X Planar Tunnel Diode

Technical Characteristics

Product Features

Rugged Germanium Planar Construction
Excellent Temperature Stability
No DC Bias Required
Wide Video Bandwidth


Product Description

EclipseMDI MBD3057-H20X, is a zero-bias, rugged Planar Tunnel Diode constructed with Germanium Planar. This tunnel diode exhibits excellent temperature stability, wide video bandwidth. The MBD3057 is also available in hermetic (H20) ceramic packages.

Maximum Ratings


Storage Temperature.....-65° to +125°C
Operating Temperature.....-65° to +110°C
Input Power Handling.....+17dBm CW
or 3 ERG spike
Soldering Temperature.....+160° C

H20X (NON-HERMETIC)




Parameters	Specifications				
	Conditions	MIN	Typical	MAX	UNITS
I_p		300		400	μA
C_j	$V_r = V_v$, $f = 100 \text{ MHz}$			.30	pF
$K[Y]$	$P_{in} = -20 \text{ dBm}$ $R_{Load} = 10K$, $f = 10 \text{ GHz}$		500		mV/mW
R_v			80		Ω Ohms
I_p/I_v		2.5			
V_r	$I_f = 500 \mu A$		400		mV
V_f	$I_f = 3 \text{ mA}$			125	mV

Diode equivalent circuit



Back diode parameters



About EclipseMDI

ECLIPSE Microdevices is located in San Jose, California. ECLIPSE has been developing high performance analog semiconductors for use in wireless radio frequency (RF), microwave, and millimeter wave for commercial and industrial applications. ECLIPSE has formed a strategic alliances - with foundries that features leading state-of-the-art process technologies and with manufacturing facilities for high-volume production of innovative RFIC's.

Product Export Classification
ECCN: EAR 99 (unless otherwise specified)
HTS: 8541.100060

